



1ST Conference on Quality Innovation and Sustainability (ICQIS)

PROCEEDINGS



Instituto Politécnico de Viana do Castelo
Escola Superior
de Ciências Empresariais

6-7 June 2019



Proceedings of the 1st Conference on Quality Innovation and Sustainability



6-7 June 2019

This Book contains the Papers as they were sent by the authors in text format to 1st ICQIS Conference.

Book printed at the Publishing Services Escola Superior de Ciências Empresariais de Valença

Cover design: Luís Barreto

ISBN: 978-989-20-9582-0

© 2019 Escola Superior de Ciências Empresariais de Valença

Editors: Luís Barreto, José Carlos Sá, Manuel Gilberto Santos

Editors

Luís Barreto, Polytechnic Institute of Viana do Castelo, Portugal

José Carlos Sá, Polytechnic Institute of Viana do Castelo, Portugal

Manuel Gilberto Santos, Polytechnic Institute of Cávado e Ave

Copyright 2019

Title: Proceedings of the 1st Conference on Quality Innovation and Sustainability.

ISBN: 978-989-20-9582-0

ISSN: 978-989-20-9582-0

Organizing Committee

José Carlos Sá (Escola Superior de Ciências Empresariais – Instituto Politécnico de Viana do Castelo, Portugal)

Luís Barreto (Escola Superior de Ciências Empresariais – Instituto Politécnico de Viana do Castelo, Portugal)

Gilberto Santos (Instituto Politécnico do Cávado e do Ave, Portugal)

Scientific Committee

NAME	AFFILIATION	COUNTRY
Alaa Hassan	Université de Lorraine	France
Alexandre Pires	Escola Superior de Tecnologia e Gestão de Águeda	Portugal
Ana Sofia Rodrigues	Instituto Politécnico de Viana do Castelo	Portugal
Anabela Alves	Universidade do Minho	Portugal
Ângela Silva	Instituto Politécnico de Viana do Castelo	Portugal
António Amaral	Universidade do Minho	Portugal
António Galvão Ramos	Instituto Superior de Engenharia do Porto	Portugal
António Mário Pereira	Politécnico de Leiria	Portugal
António Pires	Instituto Superior de Engenharia do Porto	Portugal
Carina Pimentel	Universidade de Aveiro	Portugal
Carsten Stechert	Ostfalia University of Applied Sciences	Germany
Célia Carrasqueiro	Instituto Politécnico de Coimbra	Portugal
Dercio Luis Reis	Universidade Federal do Amazonas	Brazil
Dinis Carvalho	Universidade do Minho	Portugal
Ely Sena de Almeida	Universidade Federal do Amazonas	Brazil
Federica Murmura	Università degli Studi di Urbino "Carlo Bo"	Italy
Filipa Mourão	Instituto Politécnico de Viana do Castelo	Portugal
Florbela Correia	Instituto Politécnico de Viana do Castelo	Portugal
Francisco Silva	Instituto Superior de Engenharia do Porto	Portugal
Genett Isabel Jiménez Delgado	Institución Universitaria ITSA	Colombia
Grabriela de Mattos Veroneze	Universidade Federal do Amazonas	Brazil
Helena Navas	Universidade Nova de Lisboa	Portugal
Isabel Godinho	Instituto Português da Qualidade	Portugal
Javier Fernández	Universidad de Vigo	Spain
João Bastos	Instituto Superior de Engenharia do Porto	Portugal
João Carlos Matias	Universidade de Aveiro	Portugal
Joaquim Maciel da Costa Craveiro	Universidade Federal do Amazonas	Brazil
Jorge Freixo	Instituto Politécnico de Viana do Castelo	Portugal
José André Villas Boas Mello	Centro Federal de Educação Tecnológica Celso Suckow da Fonseca	Brazil
José Pedro Domingues	Universidade do Minho	Portugal
Laura Bravi	Università degli Studi di Urbino "Carlo Bo"	Italia
Laurent Muller	Université de Lorraine	France
Luís Cesar Barbosa	Universidade Estadual Paulista	Brazil
Luís Fonseca	Instituto Superior de Engenharia do Porto	Portugal
Luís Manuel Mendonça Alves	Instituto Superior Técnico	Portugal
Luís Pinto Ferreira	Instituto Superior de Engenharia do Porto	Portugal
Manuel Caeiro	Universidad de Vigo	Spain
Manuel Doiro	Universidad de Vigo	Spain
Manuel Freitas	Instituto Politécnico de Gestão e Tecnologia de Vila Nova de Gaia	Portugal
Manuel Pereira	Instituto Politécnico de Viana do Castelo	Portugal
Manuel Pereira Lopes	Instituto Superior de Engenharia do Porto	Portugal

NAME	AFFILIATION	COUNTRY
Manuel Rui Alves	Instituto Politécnico de Viana do Castelo	Portugal
Marcelo Albuquerque de Oliveira	Universidade Federal do Amazonas	Brazil
Maria Antónia Gonçalves	Instituto Superior de Engenharia do Porto	Portugal
Maria João Félix	Instituto Politécnico do Cavado Ave	Portugal
Maria Teresa Ribeiro Pereira	Instituto Superior de Engenharia do Porto	Portugal
Maud Rio	Université Grenoble Alpes	France
Miguel Corticeiro Neves	Academia da Força Aérea	Portugal
Nuno Octávio Fernandes	Instituto Politécnico de Castelo Branco	Portugal
Otávio Jose de Oliveira	Universidade Estadual Paulista	Brazil
Pat Donnellan	National University of Ireland, Galway	Ireland
Paulo Ávila	Instituto Superior de Engenharia do Porto	Portugal
Paulo Eduardo Laranjeira	Politécnico do Porto	Portugal
Paulo Oliveira	Politécnico do Porto	Portugal
Roland Jochem	Technische Universität Berlin	Germany
Rute Maria Gomes Abreu	Instituto Politécnico da Guarda	Portugal
Sofia Gomes	Instituto Superior de Administração e Gestão	Portugal
Sónia Carvalho	Instituto Politécnico de Viana do Castelo	Portugal
Teresa Bernardino	Instituto Politécnico de Viana do Castelo	Portugal
Teresa Morgado	Centro de Instrumentação Científica - Laboratório Nacional de Engenharia Civil	Portugal
Teresa Pereira	Instituto Superior de Engenharia do Porto	Portugal
Teresa Santos Ferreira	Institute of Business Management	Portugal
Thaís V. Nunhes	Universidade Estadual Paulista	Brazil
Tiago Pinho	Instituto Politécnico de Setúbal	Portugal
Vanda Lima	Politécnico do Porto	Portugal
Venceslau Manuel Correia	Instituto Superior de Engenharia do Porto	Portugal
Wellington Alves	Instituto Politécnico de Viana do Castelo	Portugal

Preface

We are very pleased to have you participate in the 1st Conference on Quality Innovation and Sustainability – ICQIS2019 in Valença, Viana do Castelo, Portugal. The conference is being organized together with Business Sciences School of the Polytechnic Institute of Viana do Castelo. It takes place in Valença on the 6th and 7th of June 2019. Our main goal is to join together in this event academics and practitioners from a variety of fields and the dissemination of knowledge and the exchange of good practices among in the main domain of quality management, but also in innovative practices and sustainability. We expect to provide a forum of debate for researchers and practitioners, contributing to support the sharing of experiences, to promote cross-knowledge and strengthen the academic-industry relationship.

This book compiles the papers presented at the 1st Conference on Quality Innovation and Sustainability (ICQIS2019)

The Editors would like to thank all the authors and reviewers for their valuable contribution and for making ICQIS2019 such a big success.

Thank you very much for your important participation and collaboration in ICQIS2019!

Improvement of the Volumetric Occupancy Rate of the Trucks in the Warehouse-Store Transportation in a Retail Food Company

M. Enes⁽¹⁾, A. Silva^(2,3)

⁽¹⁾ Escola de Engenharia. Universidade do Minho. Guimarães, Portugal. E-mail: mariana_enes_@hotmail.com

⁽²⁾ Escola Superior de Ciências Empresariais. Instituto Politécnico de Viana do Castelo. Valença, Portugal. E-mail: angela.a@esce.ipv.pt

⁽³⁾ COMEGI, Universidade Lusíada, Vila Nova Famalicão, Portugal

ABSTRACT

This project was developed in a food retail company with a complex distribution system, with several distribution centres located in Portugal, different temperature requirements for their products and different dimension store formats. The aim of the work was to analyze procedures to increase the height of loading units to improve the volumetric occupancy rate of the trucks, which depends mainly on the relationship between the number of pallets transported in each vehicle and its volume. After analyzing and diagnosing the picking, loading and unloading operations, it was found that the volumetric occupancy rate of the vehicles was 48.5%, which means that more than half of the truck is empty. To increase this indicator, two strategies were proposed to be implemented: the revision of the current volume and weight limits; and the consolidation of different categories in the same pallet for the small format store. After conducting pilot tests, it was estimated, for each of these strategies, an increase of 0.8% on volumetric occupancy rate, and an increase of a potential gain was obtained of more than 577,908 €/year.

Keywords: Transportation, Vehicle Volumetric Occupancy, Units Load Height

1. Introduction

The great demands of an increasingly competitive market have made logistics an essential part of all companies, so one of the biggest tasks of managers is to direct all activities that contribute significantly to better customer service and the lowest cost [1].

According to Thomas & Griffin [2], the largest cost component of logistics is transportation cost, usually accounting for 50% of the total logistics cost. At a time when the global economic and financial environment forces organizations to manage their resources in the most efficient way possible, and the retail market segment is highly competitive, demanding and complex, cost management is vital to success and sustainability of the company under study.

At present, the loading units prepared in the warehouses of the company under study to transport to the stores do not have a standard height and the average of this is low. Due to this factor and to the differences in the typologies of boxes packaged in the pallets, it is not possible to overlap them, with only a floor occupancy of the vehicle and not in height, when loading and conditioning the loads on trucks. Thus, because the load units have an average height of 1 meter and since they cannot be stacked, there is a low occupancy rate of the trucks in height, resulting in high transport costs. In this sense, as transport is as more economical as the greater the capacity utilization of the vehicles, it became crucial to identify measures to improve the height of the load units.

This project was developed mainly considering a case study research strategy. The purpose of the project was to analyze the current process of picking, and loading, conditioning and unloading of trucks operations used in the warehouse-store transportation, identifying the factors that influence the height of load units, and the study and evaluation of measures to improve it.

2. Literature review

The state of the art is designed for areas such as logistics and supply chain management, transportation activity and management, and vehicle volumetric occupancy rate.

2.1 Retail supply chain configuration

Transformations in the retail supply chain have led retailers to see a restructuring of the logistics network: switching from "passive recipients of products" to "manufacturers with anticipation of demand", which currently control, organize and manage the whole chain (from production to consumption) - the current essence of retail logistics [3]. In a functional perspective, the internal retail supply chain is predominantly divided into three logistical subsystems: (a) distribution center (b) transport and (c) store (Figure 1). Since each subsystem, although with its own working and planning mechanisms, depends on the requirements of other systems, the result is a complex interrelated structure that must be considered in planning operations [4].




Figure 1. Configuration of the retail supply chain (Adapted from [4])

In the literature, there are different approaches to analyze and improve warehouse efficiency and to optimize the different processes related to the flow of material and information in the supply chain. Kłodawski et al. [5] presents problems of designing and organizing logistic processes in warehouse facilities, highlighting the need of improving logistics facilities actions as a key aspect to increase productivity, flexibility and reliability of supply chains. Shepelev et al. [6] developed a procedure for determining the optimal parameters of transport and warehouse complexes. The performance of equipment and means of internal transport and its impact on the implementation of warehouse processes was studied by Pyza et al. [7]. In their work the role of warehouse in the supply chain and its importance in the effective flow of material goods was discussed. Other authors [8] refers that it is possible to increase the efficiency of the transport-warehouse relationships in the logistics chain by determining the optimal volume of transportation and storage of goods in the logistics chain. The movement of material flow in supply chain is impossible without transport involvement.

Transport activity management can be defined as the process of planning, implementing and controlling the most effective and efficient procedures and techniques with the goal of achieving cost reduction, increasing the level of customer service and increasing optimization of the company's resources [9,10].

Thus, Lambert et al. [9] summarizes the main functions of transport managers, stating that they should select the most appropriate mode and type of vehicles, select the vehicle fleet and manage it and, on a more daily basis, plan routes, loads and vehicles. In order to ensure an efficient and logistically efficient transport subsystem, it is necessary to take into account a set of factors that influence the physical distribution of load from the warehouses to the stores, such as the distance to be traveled, time of delivery, quantity transported, non-existence of return load, dimensions and morphology of the load, degree of fragility of the load and restrictions at the point of sale.

The goal of day-to-day planning should be vehicle optimization. The Transport Optimization Report [11] identifies three main areas of improvement in terms of transport optimization: improving vehicle occupancy, reducing empty kilometers and increasing productive time as a proportion of the total time available, and stressing that each of these areas can be affected by one or more factors previously mentioned. There is a set of key performance indicators (KPIs) that can be used to measure and target each of the areas:

- Percentage of occupancy of vehicles;
- Percentage of kilometers in empty space;
- Productive time as a percentage of total available time.

2.2 Volumetric occupancy rate of vehicles

Improving vehicle volumetric occupancy rate is one of the most attractive sustainable delivery measures for companies as it provides substantial economic and environmental benefits, hence the importance of their maximization in the success of a company [12].

Traditionally, companies measure vehicle occupancy considering only the relationship between the weight of the load transported and the maximum weight of the vehicle [12]. However, as in the food retail sector products have an increasingly lower density, the weight-based occupation underestimated the true level of utilization [13]. In this sense, the occupancy of the truck is limited much more by the floor area or height of the vehicle than by the weight. A measure of occupancy that results from the product between the percentage of floor occupancy (equation 1) and the percentage of height occupancy (equation 2) is more appropriate to calculate the percentage of volumetric occupancy [13, 14]:

$$\%floor\ occupancy = \frac{\text{number of pallets transported to the ground}}{\text{Maximum number of pallets to the ground on the truck}} \quad (1)$$

$$\%height\ occupancy = \frac{\text{Load units' average height}}{\text{Maximum truck height available}} \quad (2)$$

When there are tight limits to the height of a load unit and when it is low and variable, the truck occupancy is usually restricted by the floor area rather than by the height of the vehicle and can be completely occupied on the floor by pallets with a height of 1.5 meters, leaving a meter or more of wasted space above them [14]. The study made by McKinnon and Edwards [15] reveals that companies often overuse their vehicles as a result of minimizing total logistics costs by making perfectly rational trade-offs between transport efficiency and other corporate goals such as minimizing stocks, optimizing

storage space use, or maximizing productivity preparation of orders. However, Mckinnon [14] and McKinnon and Edwards [15] examined the possibility of improving the use of vehicles, including potential economic and environmental benefits. One of the opportunities indicated was the increase of the load units' height. Generally, there are tightness volume and weight limits that restrict its height, so the increase of these limits can reduce the number of trucks required per year. This was one of the measures analysed and that will be described in the present work.

3. Study context and Critical Analysis

The company studied is one of the largest food retail companies in Portugal, with a set of distinct formats that offer a wide range of products. It essentially operates with three major players in its logistics chain: suppliers, distribution centers and stores.

It has strategically two large logistics centers, where the warehouses are located that operate in a specialized and independent way. Both platforms supply different regions of the country, with food products at ambient, fresh and frozen temperature, covering the entire national territory and the islands. In these logistical platforms two types of flows are implemented: PBL (Picking by Line) and PBS (Picking by store). The main distinguishing characteristic of these flows is the lack of storage in the PBL warehouse due to their dispatch in less than 24 hours, which means the products are received and distributed immediately by the stores, while in the PBS the products are collected of their picking locations, existing stock. The division of the articles between PBS and PBL is performed considering the rotation of the products, the quality of service of the supplier and the validity of the product itself.

Comparing the warehouses of different temperatures, there is a higher dispatch volume in the ambient temperature warehouses. For this reason and for the elaboration of this research project, the analyzed warehouses were the PBL and PBS at ambient temperature in both platforms.

In order to be able to define strategies for improvement, it became essential to frame the current situation of the company regarding the current volumetric occupancy rate of trucks and a diagnosis and analysis of the operations under study. Currently, in the company, only the percentage of floor occupancy is monitored monthly, including only the trucks of 33 pallets since the fleet is composed mostly by this type of vehicles. Thus, this indicator is used to measure vehicle occupancy efficiency, although it is not very robust since a truck can occupy 100% of the floor by load units with a height of 1 meter, leaving a lot of empty space.

In this way, the project began with the calculation of the current volumetric occupancy rate of the trucks. With an average floor occupancy rate of 84.0% and a height occupancy rate of 57.7% in 2017, an average value of 48.5% was obtained, as shown in equation 3:

$$\text{Volumetric occupancy rate} = 84.0\% \times 57.7\% = 48.5\% \quad (3)$$

Thus, it is proven that more than half of the truck is air, reinforcing the importance and necessity of improving this measure. As the variable that causes the greatest negative impact on the volumetric occupancy rate is the height occupation, the objective of the project was focused on the improvement of the latter.

Shipment to stores can be done on four types of handling units: picking pallets (euro or half pallet) and complete pallets (euro or half pallet). The picking pallets are originated by the preparation activity in the warehouses, while the complete pallets are shipped with a single item and are delivered to the store exactly in these quantities, with no preparation in the warehouse. As the picking pallets, in total, represent 68.1% of the pallets transported, it became necessary to focus the analysis on this type of handling unit to understand the factors that influenced its volume and, therefore, its height.

Both in PBL and PBS flows, when preparing load units for stores, it may break down by two factors: volume or weight. For each product category, the system has defined the maximum limit of volume and weight that a load unit can reach so that whenever an order reaches one of the limits, the picker needs to continue the preparation in a new pallet.

Currently, the volume limit, in the same flow, is the same for all categories, with the PBS limit being 15% higher than the PBL limit. Regarding the weight limit, this is the same for PBL and PBS in all categories. In this sense, it was important to compare the average volume of each category with the respective limit to identify differences and to understand the impacts of changing the parameterized limits in the system. An improvement to be implemented has gone through the revision of the current volume limits and the adjustment of it according to the average weight per box (strategy 1).

Besides that, picking pallets have, for each store format A, B and C, a weighted average volume of 1.38 m³, 1.13 m³ and 0.99 m³, respectively. The small stores (format C) are those with the lowest average volume value, and some factors have been identified that contribute to this fact. The reduced daily volumes demanded by contemporary retail, with frequent deliveries of increasingly smaller orders, associated with the fact that the company is looking for a "store friendly" logistics, preparing by category, means that only 1 pallet is prepared per day and per category, with a low volume of products. As the expansion of these stores is expected, instead of preparing the orders by category on different pallets, it has been suggested that all the categories of each flow could be consolidated on the same pallet (strategy 2).

4. Improvement Proposals and Results

The two proposed strategies and their expected results are presented below.

4.1 Revision of the current volume limits based on average weight per box

With the previous diagnosis, in particular the percentage of picking pallets, for each category, which breaks by volume, by weight or by neither of those and the average weight per box, the need arose to evaluate the impact that would have occurred if the limits parameterized changed. For the categories that mostly broke through the volume and the weight, the adjustment of the limits was studied. A change in these can enhance the placement of boxes at a higher height, so an adjustment to the average weight per box was the criterion used to consider the ergonomic conditions of the operators. Thus:

- For the categories with the smaller value of average weight per box, compared to the other categories of the same flow, increase the volume limit;
- For the remaining categories with the highest average weight per box, maintain the volume limit.

Through several pilot tests, it was possible to measure the impact of these changes in each one of the actors of the chain: warehouse, transport and store operations. By increasing the volume limits of the load units, it is possible to place more boxes on the same pallet which can consequently result in a reduction in the number of picking pallets prepared and shipped. This reduction has an impact on the floor space occupied in the warehouse and at the backroom store, on the time of loading and unloading of the trucks, as well as the associated transportation cost. Also, this increase in the limits may or may not result in an increase in the productivity of operators because, although more boxes are placed per pallet, it also increases the difficulty in the construction of the stowage, which can cause the operator to waste more time in the quality assurance.

Based on the data obtained through pilot tests, the number of picking pallets that would have been prepared were simulated by category, store and date of delivery to the store, if the limits remained the same as the current ones, and this value was compared with the number of pallets generated during the pilot tests with the proposed limits. It was found that for PBS, instead of 7,492 pallets being prepared with the current limits, 7,325 pallets were generated in the week of the pilot test, corresponding to a reduction of 2.2% in the number of pallets and so a reduction of 18,264 pallets per year. Likewise, in the PBL, instead of generating 4,976 pallets, 4,818 pallets were generated during the test period, equivalent to a reduction of 3.2% in the number of pallets and to less than 25,889 pallets per year. In total, an average reduction of 2.7% of picking pallets was estimated.

Still with the results of the pilot tests, the relation between the picking productivity and the number of boxes per pallet was analyzed to understand if the proposed changes had a significant impact and whether it was positive or negative. There was an approximately linear behavior, allowing to conclude that the bigger the number of boxes per pallet, the greater the productivity of the operators.

Finally, the impact of this scenario on the volumetric occupancy rate was estimated, corresponding to an increase of 0.8%, resulting from an increase in the percentage of height occupancy rate (+0.9%).

After calculating all the impacts of this strategy, the annual benefits in euros, associated with the changes in the proposed scenario (Figure 2), were estimated by logistic subsystem (warehouse, transport and store).




Figure 2. Estimation of the potential annual benefit of strategy 1

Observing Figure 2, this proposal has a potential benefit of 377,563 €/year, being that the transport logistics subsystem is the largest part, approximately 86.7%. This proves that, in fact, transport has a high weight in the logistics cost structure, so any solution that seeks to reduce the air inside the truck, results in a very significant impact.

Due to its enormous potential, in May 2018, this strategy was implemented, provided that its results were monitored through to a cockpit chart. Table I shows the results obtained for the indicators whose changes are directly related to the implementation of this strategy, as well as the percentage variation obtained between January and September 2018.

On indicator 2, a 2.7% increase was achieved. It is not an increase as significant as the one achieved on the indicator 2a because, as there are four handling units and since complete pallets, due to its low average volume, negatively influence the indicator 2a, an increase in the percentage of complete pallets (euro and a half) contradicts the positive impacts of this strategy.

Regarding indicator 2b, the average reduction target of 2.7% of picking pallets previously estimated has been met, translating into a potential annual benefit of 345,104 €/year.

Table I. Presentation of results obtained (January vs September) by the implementation of strategy 1

Nº	Indicator	January	September	Variation (%)
2	Height Occupancy rate (%)	56.2%	57.7%	+2.7%
2a	Average volume per pallet (m ³)	1.10	1.11	+0.9%
2b	Reduction in the number of picking pallets (%)	-	2.6%	+2.6%
2aa	Average volume per picking pallet (m ³)	1.14	1.19	+4.4%

4.2 Consolidation of the categories in the same pallet for the stores of the format C

As mentioned above, the format C stores are those with the lowest average volume per picking pallet, which is related to the fact that 1 pallet per category per day is dispatched to these stores. As the expansion of small format stores is expected, some changes have been suggested in the picking process of these stores: to increase the average volume of the pallets to these stores and, thus, increase its height, instead of these orders being prepared by category on different pallets, all categories of each flow would then be prepared on the same pallet, until one of the volume or weight limits is reached.

A pilot test was made on PBS for one store of format C. As the strategy in the previous subsection, this solution entails placing more boxes on the same pallet and therefore can reduce the number of pallets prepared and shipped to stores. This reduction has an impact on the floor space in the warehouse and at the backroom store, on the time of loading and unloading of the trucks, on the shelf replacement time in the store and on the associated transportation cost. Warehouse productivity can increase with more boxes on the same pallet, but this effect can be offset by the fact that the operator loses more time in stowage quality assurance.

With the pilot test data, the reduction in the number of pallets was calculated. For this, it was simulated, by category and date of delivery to the store, the number of pallets that would have been obtained if there was no consolidation, comparing this value with the number of pallets shipped during the test period. The impact of this solution on warehouse productivity was also analyzed, comparing the average productivity obtained in boxes per hour from January to May with that obtained in the test week, considering only the store submitted to pilot test. Finally, a visit to the chosen store was made to quantify the impact on shelf replacement time.

A reduction of 17.4% was observed in the number of pallets prepared and shipped to format C stores, which corresponds to less 24,284 pallets per year. This represents a reduction of 1.5% in the total number of picking pallets prepared.

Regarding the warehouse productivity, it was verified that it did not suffer any impact, presenting the same value without and with consolidation. With consolidation, the difficulty of constructing the stowage is increased, but the number of setups can be reduced, so the operator places more boxes per pallet in the same task, justifying this behavior.

About the shelf replacement time, with consolidation, the products of the different categories are mixed, not separated by layer. However, this additional manipulation of separating the boxes of different categories is not significant in the total shelf replacement time per pallet (0.7%).

It was also calculated the impact of this solution on the volumetric occupancy rate, with an increase of 0.8% in it, resulting from an increase in the percentage of height occupancy rate (+0.9%).

Finally, considering these impacts, it was possible to estimate the annual benefits per logistic subsystem associated with this solution (Figure 3).

This strategy has an estimated annual benefit of 200,345 €/year, and in the same way as strategy 1, it is in the transport logistics subsystem that the greatest benefit is found, approximately 89.6% of the total parcel. Since this solution presented great potential, which was recognized by the company, this strategy was extended to 20 stores and its impacts are still being evaluated, in order to have a more significant sample and, therefore, more robust results.




Figure 3. Estimation of the potential annual benefit of strategy 2

5. Conclusions

Since transportation is responsible for absorbing between one-thirds to two-thirds of the total logistics cost, and as often involves trade-offs between customer responsiveness capacity (greater frequency of supply) and chain efficiency (more trips, lower vehicles occupancy, and therefore higher transport costs), any decision-making in its management is reflected along the logistic chain.

Through the methodology of the case study, a study was carried out on the vehicle's occupancy in the warehouse-store transport, in a retail food company. Although this project involved only one study explaining the current state and future state and a comparison of costs versus benefits, strategies were identified to be implemented in the short term.

In this way, the project started by measuring the performance of the current situation, that is, by calculating the value of the volumetric occupancy rate, equal to 48.5%. This low value is due to the low height occupancy, which is around 57.7%. After a detailed analysis of the current picking, loading, conditioning and unloading operations, one of the main causes of this waste were identified: the low average volume of the transported pallets.

Thus, the improvement proposals, studied in order to measure their impact and quantify their potential, were focused on the improvement of the picking pallets height: the revision of the volume limits according to the average weight per box (strategy 1) and the consolidation of the PBS categories in the same pallet for the small stores (strategy 2). Both proposals had benefits in the floor space occupied in the warehouse and in the backroom store, in the time of loading and unloading of the trucks, as well as in the associated transport cost. Considering the estimated results for each strategy, it was obtained a total of:

- Reduction in the number of picking pallets (%): $2.7+1.5=4.2\%$
- Increase in height occupancy rate (%): $0.9+0.9=1.8\%$
- Increase in volumetric occupancy rate (%): $0.8+0.8=1.6\%$
- Estimated annual benefit: $377,563+200,345=577,908$ €/year

Although the increase in the percentage of height occupancy is not very significant, it translates into a very high annual monetary benefit, proving that in fact any small improvement in transport has a very significant impact on the efficiency of the chain. Strategy 1 was accepted and implemented by the company, while strategy 2 is being evaluated for 20 small format stores to validate these benefits. In order to monitor the results of strategy 1 on a monthly basis, a cockpit chart was constructed. It has been very advantageous because it has allowed a monitoring of the volumetric, in height and floor occupancy indicators, which until the beginning of this project was not possible and the results have been very positive, especially regarding the average volume per picking pallets and the height occupancy rate. Comparing January and September, there was an increase of 4.4% and 2.7%, respectively.

6. Acknowledgements

This research is supported by national funds through FCT - Foundation for Science and Technology, I.P., Portugal under the project UID/EMS/04005/2019.

7. References

- [1] R. Ballou. Business logistics: Importance and some research opportunities. *Gestão & Produção*, 4(2), 117–129, 1997.
- [2] D. J. Thomas, P. M. Griffin. Coordinated supply chain management. *European Journal of Operation Research*, 94(1), 1–15, 1996.
- [3] J. Fernie, L. Sparks, A. C. McKinnon. Retail logistics in the UK: past, present and future. *International Journal of Retail & Distribution Management*, 38(11/12), 894–914, 2010.
- [4] H. Kuhn, M. G. Sternbeck. Integrative retail logistics: An exploratory study. *Operations Management Research*, 6(1–2), 2–18, 2013.
- [5] M. Kłodawski, M. Jacyna, K. Lewczuk, and M. Wasiak, “The Issues of Selection Warehouse Process Strategies,” in *Procedia Engineering*, 2017, vol. 187.
- [6] V. Shepelev, Z. Almetova, O. Larin, S. Shepelev, and O. Issenova, “Optimization of the Operating Parameters of Transport and Warehouse Complexes,” *Transp. Res. Procedia*, vol. 30, pp. 236–244, 2018.
- [7] D. Pyza, R. Jachimowski, I. Jacyna-Golda, and K. Lewczuk, “Performance of Equipment and Means of Internal Transport and Efficiency of Implementation of Warehouse Processes,” *Procedia Eng.*, vol. 187, pp. 706–711, 2017.
- [8] Y. Kush, V. Skrypin, A. Galkin, K. Dolia, I. Tkachenko, and N. Davidich, “Regularities of Change of the Supply Chain Operation Efficiency, Depending on the Parameters of the Transport Process,” *Transp. Res. Procedia*, vol. 30, pp. 216–225, 2018.
- [9] D. M. Lambert, J. R. Stock, L. M. Ellram. *Fundamentals of Logistics Management*. 1998.
- [10] A. G. Novaes. *Logística e gerenciamento da cadeia de distribuição - Estratégia, Operação E Avaliação (3a Edição)*. Elsevier Editora Ltda. 2007.
- [11] E. Europe. *The Transport Optimisation Report*. 2000.
- [12] A. Mckinnon, S. Cullinane, M. Browne, A. Whiteing. *Green Logistics: Improving the environmental sustainability of Logistics*. London: Publishers, Kogan Page, 2010.
- [13] A. Mckinnon, Y. Ge, D. Leuchars. *Analysis of Transport Efficiency in the UK Food Supply Chain*. 2003.
- [14] A. Mckinnon. *Sustainable distribution: opportunities to improve vehicle loading*. School of Management and Languages, Heriot-Watt University, 2000.
- [15] A. McKinnon, J. Edwards. Opportunities for improving vehicle utilization. In *Green Logistics: Improving the Environmental Sustainability of Logistics*, 197–213, 2010. Kogan Page Publishers.